

Infinity



Discover the future of color precision with our Vividly Real Color technology. Our displays deliver stunningly realistic visuals with full coverage in AdobeRGB, REC709, sRGB, and extensive DCI-P3 support. COB technology with epoxy protection ensures exceptional durability, allowing screens to withstand environmental impacts. Additionally, Flip-Chip technology guarantees low power consumption, further enhancing efficiency and performance.

Specification

	I009	I026	I015
Pixel pitch (mm)	0.95	1.26	1.583
LED type	COB		
Cabinet Resolution (WxH)	640x360	480x270	384x216
Cabinet size (mm)	608 x 342 x 49 (27.5")		
Aspect ratio	16:9		
Net.weight/cabinet	7.0 kg		
Cabinet material	Die-casting aluminium		
Maintenance	Front		
IP Rating	Front IP40 / Rear IP20		
Driving Method	1/45	1/36	1/36
Brightness (cd/m2)	800		
Contrast ratio	20,000:1		
Refresh rate	≤ 3,840 Hz		
Color processing	14 bits		
Viewing angle (H/W)	170° / 170°		
Color temperature (K)	3,000-9,500		
Dimming Level	256		
Max./Avg. power consumption (per m2)	380 W / 160 W		
Power supply	AC100-240V, 50/60 Hz		
Operating temperature	-20°C to 40°C		
Operating humidity	10 to 80 %		
Led lifetime	100,000 hrs		
Certificates	CE; ETL; FCC Class A; Rohs		

Transtech global

This document is © 2024 Transtech EMEA GmbH. All rights reserved. All hardware and software names are trademarks and/or registered trademarks of their respective owners. Specifications are subject to change without notice. Errors and omissions excepted



TRANSTECH
www.trtled.com
info@trtled.com