OTV

Outdoor COB screen solution



Experience the next level of outdoor display technology with our Flip-Chip COB solutions. Perfectly suited for outdoor TVs and cinema screens, our innovative approach with common cathode technology significantly reduces heat generation, extends the lifespan of LEDs, and lowers power consumption. This advancement not only enhances performance but also aligns with our dedication to energy efficiency and sustainable practices.

Specification

	OTV 012	OTV 015	OTV 019
Pixel pitch (mm)	1.26	1.58	1.9
LED type	Flip Chip COB		
Screen resolution (WxH)	1,920 x 1,080		
Active screen size (WxHxD, mm)	2,432 x 1,368 x 76 (110")	3,040 x 1,710 x 76 (138")	3,648 x 2,052 x 76(165")
Overall size (WxHxD, mm)	2,444 x 2,194 x 78	3,052 x 2,536 x 78	3,660 x 2,878 x 78
Cabinet size (WxHxD, mm)	608 x 342 x 76		
Cabinet resolution (WxHxD, mm)	480 x 270	384 x 216	320 x 180
Net.weight Net.weight	180 kg	250 kg	350 kg
Cabinet material	Die-casting aluminium		
Mainteinance	Front / Rear		
IP Rating	Front IP65 / Rear IP65		
Driving method	1/27	1/22	1/15
Brightness (cd/m2)	3,000		
Contrast ratio	100,000:1		
Refresh rate	≤ 3,840 Hz		
Color processing	16 bits		
Vieing angle (H/W)	170° / 170°		
Color temperature (K)	3,000-9,500		
Dimming level	256		
Max./Avg. power consumption (per set)	2,400 W / 700 W	3,750 W / 1,100 W	5,400 W / 1,600 W
Power supply	AC100-240V, 50/60 Hz		
Operating temperature	-30°C to 50°C		
Operating humidity	10 to 90 %		
Led lifetime	100,000 hrs		
Control interface	1 x Genlock; 1x LAN; 1x HDMI in; 1x HDMI out; RS232/USB		
System	Android & Windows		
Operating equipment	Phone, iPad, PC		
Certificates	CE; ETL; FCC Class A; Rohs		

^{*} Please note that the value is currently estimated and may be subject to change.

Transtech global

This document is © 2024 Transtech EMEA GmbH. All rights reserved. All hardware and software names are trademarks and/or registered trademarks of their respective owners. Specifications are subject to change without notice. Errors and omissions excepted

