

WORKHUB

All in one LED display



Based on **Discovery II eco vision**. WORKHUB All-In-One LED Display integrates advantages of projector, trackpad, interactive whiteboard, wireless display adapter and video conferencing device. It has functions of interactive document presentation, split-screen mode, network multimedia display, AI face recognition, voice recognition, multi-screen display, and etc. It is mainly used in the fields of business conference, education training, public presentation, enterprise propaganda.

Specification

	WORKHUB DEV09	WORKHUB DEV12	WORKHUB DEV15	WORKHUB DEV19
Pixel pitch (mm)*	0.95	1.26	1.58	1.9
LED type	Flip chip SMD			
Screen resolution (W x H)	3,840 x 2,160	1,920 x 1,080		
Active screen size (WxHxD, mm)*	3,648 x 2,052 x 49	2,432 x 1,368 x 49	3,040 x 1,710 x 49	3,648 x 2,052 x 49
Active screen size (Diagonal)	165"	110"	137"	165"
Overall size (WxHxD, mm)	3,688 x 2,176.5 x 82	2,472 x 1,489.5 x 82	3,080 x 1,831.5 x 82	3,688 x 2,176.5 x 82
Cabinet size (WxHxD, mm)	608 x 342 x 49 (27.5")			
Cabinet Resolution (WxH)	640 x 360	480 x 270	384 x 216	320 x 180
Net.weight estimate**	390 kg	199.8 kg	279 kg	390 kg
Cabinet material	Die-casting aluminium			
Maintenance	Front			
IP Rating	Front IP30 / Rear IP30			
Driving Method	1/46	1/45	1/48	1/45
Brightness sustainable mode(cd/m2)	700			
Brightness (cd/m2)	1,100	2,500	1,900	1,100
Contrast ratio	7,000:1	8,000:1		
Refresh rate	≤ 3,840 Hz			
Color processing	16 bits			
Viewing angle (H/V)	160° / 160°	170° / 160°		
Color temperature (K)	3,000-9,500			
Dimming Level	256			
Max./Avg. power consumption (per m2)	220 W / 165 W	183 W / 106 W		
Power supply	AC100-240V, 50/60 Hz			
Operating temperature	-20°C to 40°C			
Operating humidity	10 to 80 %			
Led lifetime	100,000 hrs			
Control interface	1 x Genlock; 1x LAN; 1x HDMI in; 1x HDMI out; RS232/USB			
System	Android & Windows			
Certificates	CE; ETL; FCC Class A; Rohs			

* If you are interested in different screen size or pixel pitch variations please contact us.

** Please note that the value is currently estimated for the wall mounting screen.

Transtech global

This document is © 2024 Transtech EMEA GmbH. All rights reserved. All hardware and software names are trademarks and/or registered trademarks of their respective owners. Specifications are subject to change without notice. Errors and omissions excepted



TRANSTECH

www.trtled.com

info@trtled.com