

WORKHUB

All in one LED display



Based on **Discovery S.** WORKHUB All-In-One LED Display integrates advantages of projector, trackpad, interactive whiteboard, wireless display adapter and video conferencing device. It has functions of interactive document presentation, split-screen mode, network multimedia display, AI face recognition, voice recognition, multi-screen display, and etc. It is mainly used in the fields of business conference, education training, public presentation, enterprise propaganda.

Specification

	WORKHUB DS012	WORKHUB DS015	WORKHUB DS018	WORKHUB DS025
Pixel pitch (mm)*	1.25	1.56	1.875	2.5
LED type	SMD 3 in 1			
Screen resolution (W x H)	1,920 x 1,080			
Active screen size (WxHxD, mm)*	2,400 x 1,350 x 29	3,000 x 1,687.5 x 29	3,600 x 2,025 x 29	4,800 x 2,700 x 29
Active screen size (Diagonal)	108"	135"	162"	216"
Overall size (WxHxD, mm)	2,412 x 1,456 x 47	3,012 x 1,793.5 x 47	3,612 x 2,131 x 47	4,812 x 2,806 x 47
Cabinet size (WxHxD, mm)	600 x 337.5 x 29 (27")			
Cabinet Resolution (WxH)	480 x 270	384 x 216	320 x 180	240 x 135
Net.weight estimate**	91.2 kg	136.5 kg	196.2 kg	342.8 kg
Cabinet material	Die-casting aluminium			
Maintenance	Front			
IP Rating	Front IP30 / Rear IP30			
Driving Method	1/45	1/54	1/60	1/27
Brightness (cd/m2)	600	600	600	1,000
Contrast ratio	5,000:1			
Refresh rate	≤ 3,840 Hz			
Color processing	16 bits			
Viewing angle (H/V)	160° / 140°			
Color temperature (K)	3,000-9,500			
Dimming Level	256			
Max./Avg. power consumption (per m2)	1,879 W / 564 W	2,886 W / 866 W	4,009 W / 1,203 W	7,646 W / 2,294 W
Power supply	AC100-240V, 50/60 Hz			
Operating temperature	-20°C to 40°C			
Operating humidity	10 to 80 %			
Led lifetime	100,000 hrs			
Control interface	1 x Genlock; 1x LAN; 1x HDMI in; 1x HDMI out; RS232/USB			
System	Android & Windows			
Certificates	CE; ETL; FCC Class A; Rohs			

* If you are interested in different screen size or pixel pitch variations please contact us.

** Please note that the value is currently estimated for the wall mounting screen.

Transtech global

This document is © 2024 Transtech EMEA GmbH. All rights reserved. All hardware and software names are trademarks and/or registered trademarks of their respective owners. Specifications are subject to change without notice. Errors and omissions excepted



TRANSTECH

www.trtled.com

info@trtled.com